

## Series:HKK

Model	Refrigerant	Rated Voltage [V]	Frequency [Hz]	Displacement [cc]	Motor Type	Cooling Capacity		COP without R.C.		COP with R.C.		Approval	Height [mm]	Net Weight [Kg]
						ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF			
						-23.3°C	-25°C	-23.3°C	-25°C	-23.3°C	-25°C			
						[W]	[W]	[W/W]	[W/W]	[W/W]	[W/W]			
HKK55AA	R600 <sub>a</sub>	220-240	50	5.6	RSCR	93	69	-	-	1.71	1.35	VDE, CE	159	8.1
HKK70AA	R600 <sub>a</sub>	220-240	50	6.6	RSCR	117	87	-	-	1.75	1.38	VDE, CE	159	8.1
HKK80AA	R600 <sub>a</sub>	220-240	50	8.1	RSCR	136	102	-	-	1.77	1.40	VDE, CE	167	8.5
HKK95AA	R600 <sub>a</sub>	220-240	50	9.6	RSCR	168	126	-	-	1.80	1.42	VDE, CE	167	8.9
HKK12AA	R600 <sub>a</sub>	220-240	50	11.1	RSCR	198	150	-	-	1.80	1.42	VDE, CE	167	8.9
HKK12AT	R600 <sub>a</sub>	200-240	50	11.1	RSCR	202	152	-	-	1.80	1.42	VDE, CE	167	9.3
HKK12AN	R600 <sub>a</sub>	200-240	50	11.1	RSCR	199	150	-	-	1.69	1.33	VDE, CE	167	9.3
HKK12AN	R600 <sub>a</sub>	220-230	60	11.1	RSCR	234	176	-	-	1.72	1.35	VDE, CE	167	9.3