

## Series:HMK

Model	Refrigerant	Rated Voltage [V]	Frequency [Hz]	Displacement [cc]	Motor Type	Cooling Capacity		COP without R.C.		COP with R.C.		Approval	Height [mm]	Net Weight [Kg]
						ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF			
						-23.3°C	-25°C	-23.3°C	-25°C	-23.3°C	-25°C			
						[W]	[W]	[W/W]	[W/W]	[W/W]	[W/W]			
HMK70AA	R600 <sub>a</sub>	220-240	50	6.6	RSIR	116	87	1.49	1.18	-	-	VDE, CE, EAC	159	7.2
HMK80AA	R600 <sub>a</sub>	220-240	50	8.1	RSIR	136	102	1.50	1.18	-	-	VDE, CE, EAC	159	7.2
HMK95AA	R600 <sub>a</sub>	220-240	50	9.6	RSIR	167	125	1.53	1.20	-	-	VDE, CE, EAC	159	7.5
HMK12AA	R600 <sub>a</sub>	220-240	50	11.1	RSIR	198	149	1.53	1.20	-	-	VDE, CE, EAC	167	8.4
HMK95AT	R600 <sub>a</sub>	200-240	50	9.6	RSIR	167	126	1.53	1.20	-	-	CE	167	8.4