

Series:HTK

| Model | Refrigerant | Rated Voltage [V] | Frequency [Hz] | Displacement [cc] | Motor Type | Cooling Capacity | | COP without R.C. | | COP with R.C. | | Approval | Height [mm] | Net Weight [Kg] |
|---------|-------------------|-------------------|----------------|-------------------|------------|------------------|---------|------------------|---------|---------------|---------|----------|-------------|-----------------|
| | | | | | | ASHRAE | CECOMAF | ASHRAE | CECOMAF | ASHRAE | CECOMAF | | | |
| | | | | | | -23.3°C | -25°C | -23.3°C | -25°C | -23.3°C | -25°C | | | |
| | | | | | | [W] | [W] | [W/W] | [W/W] | [W/W] | [W/W] | | | |
| HTK55AA | R600 _a | 220-240 | 50 | 5.6 | RSIR/RSCR | 93 | 69 | 1.55 | 1.21 | 1.61 | 1.25 | VDE, CE | 159 | 7.8 |
| HTK70AA | R600 _a | 220-240 | 50 | 6.6 | RSIR/RSCR | 117 | 87 | 1.61 | 1.25 | 1.66 | 1.30 | VDE, CE | 159 | 7.8 |
| HTK80AA | R600 _a | 220-240 | 50 | 8.1 | RSIR/RSCR | 136 | 102 | 1.61 | 1.26 | 1.66 | 1.31 | VDE, CE | 159 | 7.9 |
| HTK95AA | R600 _a | 220-240 | 50 | 9.6 | RSIR/RSCR | 167 | 126 | 1.64 | 1.29 | 1.70 | 1.34 | VDE, CE | 167 | 8.3 |
| HTK12AA | R600 _a | 220-240 | 50 | 11.1 | RSIR/RSCR | 198 | 149 | 1.64 | 1.28 | 1.70 | 1.34 | VDE, CE | 167 | 8.4 |