

## Series:HTK

| Model   | Refrigerant       | Rated Voltage [V] | Frequency [Hz] | Displacement [cc] | Motor Type | Cooling Capacity |         | COP without R.C. |         | COP with R.C. |         | Approval | Height [mm] | Net Weight [Kg] |
|---------|-------------------|-------------------|----------------|-------------------|------------|------------------|---------|------------------|---------|---------------|---------|----------|-------------|-----------------|
|         |                   |                   |                |                   |            | ASHRAE           | CECOMAF | ASHRAE           | CECOMAF | ASHRAE        | CECOMAF |          |             |                 |
|         |                   |                   |                |                   |            | -23.3°C          | -25°C   | -23.3°C          | -25°C   | -23.3°C       | -25°C   |          |             |                 |
|         |                   |                   |                |                   |            | [W]              | [W]     | [W/W]            | [W/W]   | [W/W]         | [W/W]   |          |             |                 |
| HTK55AA | R600 <sub>a</sub> | 220-240           | 50             | 5.6               | RSIR/RSCR  | 93               | 69      | 1.55             | 1.21    | 1.61          | 1.25    | VDE, CE  | 159         | 7.8             |
| HTK70AA | R600 <sub>a</sub> | 220-240           | 50             | 6.6               | RSIR/RSCR  | 117              | 87      | 1.61             | 1.25    | 1.66          | 1.30    | VDE, CE  | 159         | 7.8             |
| HTK80AA | R600 <sub>a</sub> | 220-240           | 50             | 8.1               | RSIR/RSCR  | 136              | 102     | 1.61             | 1.26    | 1.66          | 1.31    | VDE, CE  | 159         | 7.9             |
| HTK95AA | R600 <sub>a</sub> | 220-240           | 50             | 9.6               | RSIR/RSCR  | 167              | 126     | 1.64             | 1.29    | 1.70          | 1.34    | VDE, CE  | 167         | 8.3             |
| HTK12AA | R600 <sub>a</sub> | 220-240           | 50             | 11.1              | RSIR/RSCR  | 198              | 149     | 1.64             | 1.28    | 1.70          | 1.34    | VDE, CE  | 167         | 8.4             |