

Series:HXX

Model	Refrigerant	Rated Voltage [V]	Frequency [Hz]	Displacement [cc]	Motor Type	Cooling Capacity		COP without R.C.		COP with R.C.		Approval	Height [mm]	Net Weight [Kg]
						ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF			
						-23.3°C	-25°C	-23.3°C	-25°C	-23.3°C	-25°C			
						[W]	[W]	[W/W]	[W/W]	[W/W]	[W/W]			
HXX55AA	R600 _a	220-240	50	5.6	RSCR	97	72	-	-	1.83	1.45	VDE, CE	167	8.2
HXX70AA	R600 _a	220-240	50	6.6	RSCR	118	88	-	-	1.86	1.47	VDE, CE	167	8.4
HXX80AA	R600 _a	220-240	50	8.1	RSCR	140	105	-	-	1.90	1.50	VDE, CE	167	8.4
HXX95AA	R600 _a	220-240	50	9.6	RSCR	171	129	-	-	1.91	1.51	VDE, CE	167	8.6
HXX12AA	R600 _a	220-240	50	11.1	RSCR	202	152	-	-	1.90	1.50	VDE, CE	167	9.4
HXX95AT	R600 _a	200-240	50	9.6	RSCR	171	129	-	-	1.88	1.48	VDE, CE	167	9.3