

Series:HXK

| Model | Refrigerant | Rated Voltage [V] | Frequency [Hz] | Displacement [cc] | Motor Type | Cooling Capacity | | COP without R.C. | | COP with R.C. | | Approval | Height [mm] | Net Weight [Kg] |
|---------|-------------------|-------------------|----------------|-------------------|------------|------------------|---------|------------------|---------|---------------|---------|----------|-------------|-----------------|
| | | | | | | ASHRAE | CECOMAF | ASHRAE | CECOMAF | ASHRAE | CECOMAF | | | |
| | | | | | | -23.3°C | -25°C | -23.3°C | -25°C | -23.3°C | -25°C | | | |
| | | | | | | [W] | [W] | [W/W] | [W/W] | [W/W] | [W/W] | | | |
| HXK55AA | R600 _a | 220-240 | 50 | 5.6 | RSCR | 97 | 72 | - | - | 1.83 | 1.45 | VDE, CE | 167 | 8.2 |
| HXK70AA | R600 _a | 220-240 | 50 | 6.6 | RSCR | 118 | 88 | - | - | 1.86 | 1.47 | VDE, CE | 167 | 8.4 |
| HXK80AA | R600 _a | 220-240 | 50 | 8.1 | RSCR | 140 | 105 | - | - | 1.90 | 1.50 | VDE, CE | 167 | 8.4 |
| HXK95AA | R600 _a | 220-240 | 50 | 9.6 | RSCR | 171 | 129 | - | - | 1.91 | 1.51 | VDE, CE | 167 | 8.6 |
| HXK12AA | R600 _a | 220-240 | 50 | 11.1 | RSCR | 202 | 152 | - | - | 1.90 | 1.50 | VDE, CE | 167 | 9.4 |
| HXK95AT | R600 _a | 200-240 | 50 | 9.6 | RSCR | 171 | 129 | - | - | 1.88 | 1.48 | VDE, CE | 167 | 9.3 |